

Shade Sail Accessories Check List - Making it easy for you

Indication of turnbuckle sizes to use, this is a guide and turnbuckle size may also be determined on how much room you have from your fixing point to your shade sail.

6mm - Small shade sails up to 3x4m rectangle or 4x4x4m triangle














8mm - Medium shade sails up to 4x5 rectangle or 6x6x6m triangle

10mm - Large shade sails over 4x5m rectangle or 6x6x6m triangle



Code	Turnbuckles Electropolished - 316 High quality marine grade stainless steel
6MM	
<input type="checkbox"/> ODS-HE06	6mm Turnbuckle Hook Eye Length 155mm min - 220mm max
<input type="checkbox"/> ODS-HH06	6mm Turnbuckle Hook Hook Length 170mm min - 220mm max
<input type="checkbox"/> ODS-EE06	6mm Turnbuckle Eye Eye Length 156mm min - 215mm max
	above for use with 6mm shackles
8MM	
<input type="checkbox"/> ODS-HE08	8mm Turnbuckle Hook Eye Length 210mm min - 295mm max
<input type="checkbox"/> ODS-EE08	8mm Turnbuckle Eye Eye Length 210mm min - 295mm max
<input type="checkbox"/> ODS-HH08	8mm Turnbuckle Hook Hook Length 210mm min - 290mm max
	above for use with 8mm shackles or 8mm snap spring hooks
10MM	
<input type="checkbox"/> ODS-HH10	10mm Turnbuckle Hook Hook Length 255mm min - 350mm max
<input type="checkbox"/> ODS-HE10	10mm Turnbuckle Hook Eye Length 255mm min - 360mm max
<input type="checkbox"/> ODS-EE10	10mm Turnbuckle Eye Eye Length 255mm min - 350mm max
Rigging Screw Turnbuckles - 316 High quality marine grade stainless steel	
<input type="checkbox"/> ODS-RSJJ06	6mm Turnbuckle Rigging Screw Jaw Jaw Length 148 min - 233 max
<input type="checkbox"/> ODS-RSJJ08	8mm Turnbuckle Rigging Screw Jaw Jaw Length 178mm min - 276 max
<input type="checkbox"/> ODS-RSJJ10	10mm Turnbuckle Rigging bottle screw min 220mm - 230mm max
	above for use with 8mm, 10mm shackles & 8mm snap spring hooks
Eyebolts/Eye Nut Bolts - 316 High Quality marine grade stainless steel	
(Eyebolts come in 8mm, 10mm, 12mm this is the thickness of the eyebolt. Collared eyebolts fit flush with a square pole.)	
EyeBolt Measurements (L = Thread, L1 = Neck, L2 = Overall Length)	
Measurements (L = Thread, L1 = Overall Length)	
M8	
<input type="checkbox"/> ODS-08035304	Eyebolt M8 8mm L = 25, L1 = 35, L2 = 74 (304)
<input type="checkbox"/> ODS-08060	Eyebolt M8 8mm L = 55, L1 = 60, L2 = 92
<input type="checkbox"/> ODS-08080	Eyebolt M8 8mm L = 70, L1 = 80, L2 = 133
<input type="checkbox"/> ODS-08100	Eyebolt M8 8mm L = 90, L1 = 100, L2 = 132
<input type="checkbox"/> ODS-08120	Eyebolt M8 8mm L = 110, L1 = 120, L2 = 153
<input type="checkbox"/> ODS-DN08	Dome Nut 8mm
M10	
<input type="checkbox"/> ODS-10060	Eyebolt M10 10mm L = 55, L1 = 60, L2 = 104
<input type="checkbox"/> ODS-10080	Eyebolt M10 10mm L = 70, L1 = 80, L2 = 123
<input type="checkbox"/> ODS-10120	Eyebolt M10 10mm L = 110, L1 = 120, L2 = 163
<input type="checkbox"/> ODS-10150	Eyebolt M10 10mm L = 125, L1 = 150, L2 = 195
<input type="checkbox"/> ODS-10170	Eyebolt M10 10mm L = 160, L1 = 170, L2 = 212
<input type="checkbox"/> ODS-ENB10100	Eye Nut Bolt M10 10mm L = 100, L1 = 150 (with collar)
<input type="checkbox"/> ODS-ENB10120	Eye Nut Bolt M10 10mm L = 120, L1 = 165 (with collar)
<input type="checkbox"/> ODS-ENB10160	Eye Nut Bolt M10 10mm L = 160, L1 = 210 (with collar)

<input type="checkbox"/>	ODS-ENB10200	Eye Nut Bolt M10 10mm L = 200, L1 = 250 (with collar)	
<input type="checkbox"/>	ODS-DN10	Dome Nut 10mm	
	M12		
<input type="checkbox"/>	ODS-12120	Eyebolt M12 12mm L = 110, L1 = 120, L2 = 170	
<input type="checkbox"/>	ODS-12185	Eyebolt M12 12mm L = 145, L1 = 185, L2 = 235	
<input type="checkbox"/>	ODS-ENB12100	Eye Nut Bolt M12 10mm L = 100, L1 = 160 (with collar)	
<input type="checkbox"/>	ODS-ENB12150	Eye Nut Bolt M12 10mm L = 150, L1 = 210 (with collar)	
<input type="checkbox"/>	ODS-ENB12200	Eye Nut Bolt M12 10mm L = 200, L1 = 260 (with collar)	
<input type="checkbox"/>	ODS-DN12	Dome Nut 12mm	
		Above 12mm eyebolts are not suitable with 6mm shackles or 8mm snap hooks	
		Welded Screw Eye / Eye Nut Screw (with collar)	
		Measurements (L2 = Thread, L = Neck, L1 = Overall Length)	
	M6		
<input type="checkbox"/>	ODS-06060	Eye Nut Screw M6 8mm L = 60, L1 = 93, L2 = 35 (with collar)	
<input type="checkbox"/>	ODS-ENS08080	Eye Nut Screw M8 8mm L = 80, L1 = 121 L2 = 48 (with collar)	
<input type="checkbox"/>	ODS-ENS10080	Eye Nut Screw M10 10mm L = 80 L1 = 132 = 48 (with collar)	
<input type="checkbox"/>	ODS-WSE08080	Welded Screw Eye M8 8mm L = 80, L1 = 116, L2 = 55	
<input type="checkbox"/>	ODS-WSE08130	Welded Screw Eye M8 8mm L = 130, L1 = 165, L2 = 67	
<input type="checkbox"/>			
	M10		
<input type="checkbox"/>	ODS-WSE10060	Welded Screw Eye M10 10mm L = 60 L1 = 106 L2 = 50	
<input type="checkbox"/>	ODS-WSE10080	Welded Screw Eye M10 10mm L = 80 L1 = 125 L2 = 55	
<input type="checkbox"/>	ODS-WSE10100	Welded Screw Eye M10 10mm L = 100 L1 = 143 L2 = 65	
<input type="checkbox"/>	ODS-WSE10130	Welded Screw Eye M10 10mm L = 130 L1 = 175 L2 = 70	
<input type="checkbox"/>	ODS-WSE10150	Welded Screw Eye M10 10mm L = 150 L1 = 193 L2 = 90	
	M12		
<input type="checkbox"/>	ODS-ENS12100	Eye Nut Screw M12 12mm L = 100, L1 = 165, L2 = 62 (with collar)	
<input type="checkbox"/>	ODS-ENS12140	Eye Nut Screw M12 12mm L = 140, L1 = 205, L2 = 85 (with collar)	
<input type="checkbox"/>	ODS-ENS12160	Eye Nut Screw M12 12mm L = 160, L1 = 225, L2 = 98 (with collar)	
		Eye Bolt with Collar	
<input type="checkbox"/>	ODS-08	Eyebolt M8 8mm L = 18mm L1 = 50mm (with collar)	
<input type="checkbox"/>	ODS-10	Eyebolt M10 10mm L = 18mm L1 = 63mm (with collar)	
<input type="checkbox"/>	ODS-12	Eyebolt M12 12mm L = 20mm L1 = 75mm (with collar)	
		Pad Eyes 304 stainless steel & Wall Plates	
<input type="checkbox"/>	ODS-DEP060	Pad Eye Diamond 6mm Length 67mm, Width 48mm, Height 18mm	
<input type="checkbox"/>	ODS-DEP080	Pad Eye Diamond 8mm Length 80mm, Width 48mm, Height 30mm	
<input type="checkbox"/>	ODS-DEP090	Pad Eye Diamond 9mm Length 89mm, Width 57mm, Height 23mm	
<input type="checkbox"/>	ODS-DEP100	Pad Eye Diamond 10mm Length 100mm, Width 60mm, Height 26mm	
<input type="checkbox"/>	ODS-REP06	Pad Eye Rectangle 6mm Length 40mm, Width 34mm, Height 23mm	

<input type="checkbox"/>	ODS-REP08	Pad Eye Rectangle 8mm Length 50mm, Width 39mm, Height 29mm	
<input type="checkbox"/>	ODS-REP10	Pad Eye Rectangle 10mm Length 60mm, Width 38mm, Height 38mm	
<input type="checkbox"/>	ODS-OEP08	Pad Eye Oblong 8mm Height 31mm Width 25mm length 81mm	
<input type="checkbox"/>	ODS-OEP09	Pad Eye Oblong 9mm Height 33mm Width 32mm length 100mm	
<input type="checkbox"/>	ODSDD	Pad Eye Diamond Wall Plate Extra large 180mm x 110mm (316 stainless steel)	
<input type="checkbox"/>	ODS100H	Wall plate galvanized horizontal 100mm x 100mm (galvanised)	
<input type="checkbox"/>	ODS150H	Wall plate galvanized horizontal 150mm x 150mm (galvanised)	
<input type="checkbox"/>	ODS100D	Wall plate galvanized diagonal 100mm x 100mm (galvanised)	
<input type="checkbox"/>	ODS150D	Wall plate galvanized diagonal 150mm x 150mm (galvanised)	
<input type="checkbox"/>	ODS100HStainless	Wall plate Stainless Steel horizontal 100mm x 100mm (Stainless Steel)	
<input type="checkbox"/>	ODS150HStainless	Wall plate Stainless Steel horizontal 150mm x 150mm (Stainless Steel)	
		Pad eyes and wall plates are available in different sizes. The standard size is 8mm but larger ones may be suitable if you have a large shade sail or need better structural support as the large size will distribute the load over a wider area.	
		Fixing and extending 316 Marine grade stainless steel (Cast and Forged)	
<input type="checkbox"/>	ODS-FDS06	Dee Shackle 6mm Forged Length 36mm, Width 22mm, Opening 13mm	
<input type="checkbox"/>	ODS-FDS08	Dee Shackle 8mm Forged Length 48mm, Width 29mm, Opening 17mm	
<input type="checkbox"/>	ODS-FDS10	Dee Shackle 10mm Forged Length 60mm, Width 36mm, Opening 21mm	
<input type="checkbox"/>	ODS-CLDS08	Dee Shackle 8mm (long) - Length 79mm Width 30mm Opening 16mm	
<input type="checkbox"/>	ODS-CLDS10	Dee Shackle 10mm (long) - Length 99 width 40 opening 23mm	
<input type="checkbox"/>	ODS-CTDS06	Cast Twist Shackle 6mm Length 47mm, Width 22mm, Opening 12mm	
<input type="checkbox"/>	ODS-CTDS08	Cast Twist Shackle 8mm Length 59mm, Width 30mm, Opening 16mm	
<input type="checkbox"/>	ODS-CTS10	Cast Twist shackle 10mm Length 69mm, Width 46mm, Opening 20mm	
<input type="checkbox"/>	ODS-CLTDS06	Twist shackle 6mm (long) Length 60mm, Width 33mm, Opening 12mm	
<input type="checkbox"/>	ODS-CLTDS08	Twist shackle 8mm (long) Length 83mm width 64mm Opening 17mm	
<input type="checkbox"/>	ODS-CLTDST10	Twist shackle 10mm (long) Length 100mm, Width 76mm, Opening 19mm	
<input type="checkbox"/>	ODS-FBS06	Forged Bow Shackle 6mm Length 46mm, Width 21mm, Opening 12mm	
<input type="checkbox"/>	ODS-FBS08	Forged Bow Shackle 8mm Length 56mm, Width 26mm, Opening 16mm	
<input type="checkbox"/>	ODS-FBS10	Forged Bow Shackle 10mm Length 70mm, Width 34mm, Opening 21mm	
<input type="checkbox"/>	ODS-FBS12	Forged Bow Shackle 12mm Length 88mm, Width 40mm, Opening 25mm	
<input type="checkbox"/>	ODS-SH06	Snap Hook 6mm Length 60mm width 30mm	
<input type="checkbox"/>	ODS-SH08	Snap hook 8mm length 80mm width 40mm	
<input type="checkbox"/>	ODS-SH10	Snap Hook 10mm Length 100mm Width 59mm	
<input type="checkbox"/>	ODS-W4	Wire 4mm includes 2 rope grips sold by the metre (7x19 strand rope)	
<input type="checkbox"/>	THIMBLES4MM	Thimbles 4mm	
<input type="checkbox"/>	ODS-4WRG	Rope Grip 4mm	
		Chain High quality marine grade stainless steel	

		Sold by the metre	
<input type="checkbox"/>	ODS-304-04M	Chain 4mm 304 stainless steel	
<input type="checkbox"/>	ODS-316-04M	Chain 4mm 316 stainless steel	
		above not suitable for use with 8mm shackles or snap hooks, use 6mm d shackles	
<input type="checkbox"/>	ODS-304-06M	Chain 6mm 304 stainless steel	
<input type="checkbox"/>	ODS-316-06M	Chain 6mm 316 stainless steel	
		above suitable for use with 8mm & 10mm accessories	
		Fascia and Rafter brackets - Galvanised Steel	
<input type="checkbox"/>	FB-R or FB-L	Fascia bracket Right or Left - 280mm x 110mm	
<input type="checkbox"/>	FB-90	Fascia bracket 90° - 300mm x 100mm	
<input type="checkbox"/>	ODS-RB1	Rafter bracket 16mm assembly M16 nut 210mm x 75mm Rod extends 290mm	
		8mm or 10mm shackles (excluding snap spring hook) can be used with M16 rafter brackets	
<input type="checkbox"/>	ODS-RB2	(backing plate) for Rafter16mm assembly	
<input type="checkbox"/>	ODS-RB250	Rafter bracket 20mm assembly M20 nut 300mm x 75mm Rod extends 350mm	
		10mm d shackle can be used with M20 rafter bracket	
<input type="checkbox"/>	ODS-RB5	Corrugated Rafter Bracket	
<input type="checkbox"/>	ODS-10	Eyebolt M10 10mm L = 18mm L1 = 63mm (with collar)	
<input type="checkbox"/>	ODS-RB3	Fascia bracket assembly 12mm thread includes M12 eye nut	
		above use with 8mm shackles (excluding snap spring hook)	
<input type="checkbox"/>	ODS-RB4	(backing plate) for fascia12mm 20mm rafter bracket	
<input type="checkbox"/>	ODS-INT100GAL	Corner Internal bracket 100mm X 100mm Galvanised	
<input type="checkbox"/>	ODS-INT100SS	Corner Internal bracket 100mm X 100mm Stainless Steel	
<input type="checkbox"/>	ODS-EXT100GAL	Corner External bracket 100mm X 100mm Galvanised	
<input type="checkbox"/>	ODS-EXT100SS	Corner External bracket 100mm X 100mm Stainless Steel	
<input type="checkbox"/>	ODS-INT250GAL	Corner Internal bracket 250mm X 250mm Galvanised	
<input type="checkbox"/>	ODS-INT250SS	Corner Internal bracket 250mm X 250mm Stainless Steel	
<input type="checkbox"/>	ODS-EXT250GAL	Corner External bracket 250mm X 250mm Galvanised	
<input type="checkbox"/>	ODS-EXT250SS	Corner External bracket 250mm X 250mm Stainless Steel	
		above corner brackets can be used with 8mm shackles (excluding snap spring hook)	
<input type="checkbox"/>	ODS-DEK99BLACK	Dektite Flashing 0-35mm suitable for aluminium roofs (BLACK)	
<input type="checkbox"/>	ODS-DEK99GREY	Dektite Flashing 0-35mm suitable for aluminium roofs (GREY)	
<input type="checkbox"/>	ODS-DEK135BLACK	Dektite Flashing 5-55mm suitable for aluminium roofs (BLACK)	
<input type="checkbox"/>	ODS-DEK100B	Dektite Flashing suitable for tiled roofs	
<input type="checkbox"/>	ODSDEKABB	Dektite Flashing suitable for tiled roofs	
<input type="checkbox"/>	ODS-STUD150	Stud Wall Bracket 150mm x 40mm Galvanised	

(Please note if you are unsure of the structural support you will need for installation of your shade sail please consult a qualified person for advise)

www.theshadesailshop.com.au

2/165 Blackwall Road Woy Woy 2256 NSW 02 4326 1813

The Shade Sail Shop ABN 49 142 056 586